



1nm stbd, black anodized

101-001-B

1nm stbd, black anodized
Vertically mounted with 2,5m cable

Specifications	
Number	101-001-B
Light Color	Green
Dimensions metric	92,5 x 28 x 49,7
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>1.2cd
Dimensions imperial	3.6" x 1.1" x 1.95"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	1nm
Included In Package	1 Navigation light, precabled with 2.5 meter shielded marine grade cable, Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438010284
IP rating	IP68
Power draw (W)	1,1
UPC Code	879343010287
Connection	2.5m cable

Specifications

Current consumption (mA @ 12VDC)	66
---	----

Current consumption (mA @ 24VDC)	34
---	----

Vessel size	Under 12M
--------------------	-----------

Min. feed wire gauge	0.5mm ² AWG22
-----------------------------	--------------------------

Weight (Kg)	0.39 Kg
--------------------	---------

Weight (Oz)	13.76 Oz
--------------------	----------