



## 1nm port, black anodized

101-002-B

1nm port, black anodized  
Vertically mounted with 2,5m cable

Specifications	
Number	101-002-B
Light Color	Red
Dimensions metric	92,5 x 28 x 49,7
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
Intensity	>1.2cd
Dimensions imperial	3.6" x 1.1" x 1.95"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	1nm
Included In Package	1 Navigation light, precabled with 2.5 meter shielded marine grade cable, Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438009943
IP rating	IP68
Power draw (W)	1,1
UPC Code	879343009946
Connection	2.5m cable

Specifications	
<b>Current consumption (mA @ 12VDC)</b>	60
<b>Current consumption (mA @ 24VDC)</b>	32
<b>Vessel size</b>	Under 12M
<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
<b>Weight (Kg)</b>	0.39 Kg
<b>Weight (Oz)</b>	13.76 Oz