



Tri-anchor, Windex mnt+light, Silver w/FB base

101-009W-FB

Tri-anchor, Windex mnt+light, Silver w/FB base
Horizontally mounted with 0,75m cable
Illuminated Windex mount

Specifications	
Number	101-009W-FB
Light Color	Red,Green,White
Dimensions metric	Ø92,5mm x 86mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Dimensions imperial	Ø3.6" x 3.3"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	1nm
Included In Package	1 Navigation light,Installation guide,precabled with 0.75 meter shielded marine grade cable
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438042704
IP rating	IP68
Power draw (W)	2.6
UPC Code	879343042837
Connection	0.7m cable
Current consumption (mA @ 12VDC)	150

Specifications

Current consumption (mA @ 24VDC)	81
---	----

Vessel size	Under 12M
--------------------	-----------

Min. feed wire gauge	0.5mm ² AWG22
-----------------------------	--------------------------

Weight (Kg)	0 Kg
--------------------	------

Weight (Oz)	0.00 Oz
--------------------	---------