



2nm 180° Red, silver anodized, with 0,7m cable

200-016G2

2nm 180° Red, silver anodized
Vertical mounted with 0.75m cable

Specifications	
Number	200-016G2
Light Color	Red
Dimensions metric	104 mm x 37 mm x 45 mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>5.4cd
Dimensions imperial	4.0" x 1.4" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light, precabled with 0.75 meter shielded marine grade cable, Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438012158
IP rating	IP68
Power draw (W)	1,5
UPC Code	879343012151
Connection	0.7m cable

Specifications	
Current consumption (mA @ 12VDC)	145
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	60
Vessel size	Under 12M,12-20M,20-50M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	0.27 Kg
Weight (Oz)	9.49 Oz