



2nm 180° Green, silver anodized

200-018G2

2nm 180° Green, silver anodized
Vertical mounted with 0.75m cable

| Specifications | |
|-----------------------|--|
| Number | 200-018G2 |
| Light Color | Green |
| Dimensions metric | 104 mm x 37 mm x 45 mm |
| Certification | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support |
| Intensity | >5.4cd |
| Dimensions imperial | 4.0" x 1.4" x 1.8" |
| Approved to | COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR |
| Visibility | 2nm |
| Included In Package | 1 Navigation light, precabled with 0.75 meter shielded marine grade cable, Installation guide |
| Operating temperature | -25°C to 55°C |
| Mounting | Horizontal |
| Materials | Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane |
| Operating Voltage | 10-32VDC |
| EAN | 5704438020405 |
| IP rating | IP68 |
| Power draw (W) | 1,5 |
| UPC Code | 879343020538 |
| Connection | 6m cable |

| Specifications | |
|---|--------------------------|
| Current consumption (mA @ 12VDC) | 145 |
| Stock status | Made to order |
| Current consumption (mA @ 24VDC) | 60 |
| Vessel size | Under 12M,12-20M,20-50M |
| Min. feed wire gauge | 0.5mm ² AWG22 |
| Weight (Kg) | 0.27 Kg |
| Weight (Oz) | 9.49 Oz |