



3nm 225° Masthead+6W decklight, silver anodized, vertical mount, with 15m cable

201-011DLX 15M

3nm masthead+6W decklight, silver anodized
Vertically mounted with 15m cable

| Specifications | |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number | 201-011DLX 15M |
| Light Color | White |
| Dimensions metric | 54 x 38,7 x 72,2 |
| Certification | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support |
| Intensity | >15cd |
| Dimensions imperial | 2.1" x 1.5" x 2.8" |
| Approved to | COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR |
| Visibility | 3nm |
| Included In Package | 1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide |
| Operating temperature | -25°C to 55°C |
| Mounting | Vertical |
| Materials | Anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane |
| Operating Voltage | 10-32VDC |
| EAN | 5704438012578 |
| IP rating | IP68 |
| Power draw (W) | 3 |
| UPC Code | 879343012571 |
| Connection | 15m cable |

| Specifications | |
|-----------------------------------------|--------------------------|
| Current consumption (mA @ 12VDC) | 232 |
| Stock status | Usually in stock |
| Current consumption (mA @ 24VDC) | 127 |
| Vessel size | 12-20M |
| Min. feed wire gauge | 0.5mm ² AWG22 |
| Weight (Kg) | 1.43 Kg |
| Weight (Oz) | 50.44 Oz |