



## 3nm 225° Masthead, double, black anodized, vertical mount, with 0,7m cable

201-011ST-B

3nm dbl masthead, black anodized  
Vertically mounted with 0,75m cables

Specifications	
Number	201-011ST-B
Light Color	White
Dimensions metric	92,5 x 88,6 x 85
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
Intensity	>15cd
Dimensions imperial	3.6" x 3.4" x 3.3"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438012707
IP rating	IP68
Power draw (W)	3
UPC Code	879343012700
Connection	0.7m cable
Current consumption (mA @ 12VDC)	232

Specifications	
<b>Stock status</b>	Usually in stock
<b>Current consumption (mA @ 24VDC)</b>	127
<b>Vessel size</b>	12-20M
<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
<b>Weight (Kg)</b>	0.99 Kg
<b>Weight (Oz)</b>	34.92 Oz