



2nm 360° White, Double, silver w/FB base

201-012ST-FB

2nm 360° White, Double, silver w/FB base
Horizontally mounted with 0,75m cable

Specifications	
Number	201-012ST-FB
Light Color	White
Dimensions metric	Ø92,5mm x 58mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Dimensions imperial	Ø3.6" x 2.3"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,Installation guide,precabled with 0.75 meter shielded marine grade cable
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438042940
IP rating	IP68
Power draw (W)	2,6
UPC Code	879343043070
Connection	0.7m cable
Current consumption (mA @ 12VDC)	167

Specifications

**Current consumption
(mA @ 24VDC)** 110

Vessel size Under 12M,12-20M,20-50M

Min. feed wire gauge 0.5mm² AWG22

Weight (Kg) 0 Kg

Weight (Oz) 0.00 Oz