



2nm 360° Red, Dbl, silver w/FB base

201-014ST-FB

2nm 360° Red, Dbl, silver w/FB base
Horizontal mounted with 0.75m cables

| Specifications | |
|----------------------------------|--|
| Number | 201-014ST-FB |
| Light Color | Red |
| Dimensions metric | Ø92,5mm x 58mm |
| Certification | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support |
| Dimensions imperial | Ø3.6" x 2.3" |
| Approved to | COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR |
| Visibility | 2nm |
| Included In Package | 1 Navigation light,Installation guide,precabled with 0.75 meter shielded marine grade cable |
| Operating temperature | -25°C to 55°C |
| Mounting | Horizontal |
| Materials | Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane |
| Operating Voltage | 10-32VDC |
| EAN | 5704438043084 |
| IP rating | IP68 |
| Power draw (W) | 2,1 |
| UPC Code | 879343043216 |
| Connection | 0.7m cable |
| Current consumption (mA @ 12VDC) | 150 |

Specifications

| | |
|---|----|
| Current consumption (mA @ 24VDC) | 85 |
|---|----|

| | |
|--------------------|-------------------------|
| Vessel size | Under 12M,12-20M,20-50M |
|--------------------|-------------------------|

| | |
|-----------------------------|--------------------------|
| Min. feed wire gauge | 0.5mm ² AWG22 |
|-----------------------------|--------------------------|

| | |
|--------------------|------|
| Weight (Kg) | 0 Kg |
|--------------------|------|

| | |
|--------------------|---------|
| Weight (Oz) | 0.00 Oz |
|--------------------|---------|