



5nm 225° Masthead, black anodized, horizontal mount, with plug connector

300-036-B

5nm masthead, black anodized
Horizontally mounted on a CSCD promount (400-034-B)

| Specifications | |
|----------------------------------|--|
| Number | 300-036-B |
| Light Color | White |
| Dimensions metric | Ø92,5mm x 111,8mm |
| Certification | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support |
| Intensity | >52cd |
| Dimensions imperial | Ø3.6" x 4.4" |
| Approved to | COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR |
| Visibility | 5nm |
| Operating temperature | -25°C to 55°C |
| Mounting | Horizontal |
| Materials | Black anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane |
| Operating Voltage | 20-32VDC |
| EAN | 5704438003316 |
| IP rating | IP68 |
| Power draw (W) | 7 |
| UPC Code | 879343003319 |
| Connection | Plug connector |
| Current consumption (mA @ 12VDC) | 0 |

Specifications

**Current consumption
(mA @ 24VDC)** 290

Vessel size 20-50M

Min. feed wire gauge 0.5mm² AWG22

Weight (Kg) 1.32 Kg

Weight (Oz) 46.56 Oz