



5nm 225° Masthead, silver anodized, horizontal mount, with plug connector

300-036

5nm masthead, silver anodized
Horizontally mounted on a CSCD pro mount (400-034).

Specifications	
Number	300-036
Light Color	White
Dimensions metric	Ø92,5mm x 111,8mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>52cd
Dimensions imperial	Ø3.6" x 4.4"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	5nm
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	20-32VDC
EAN	5704438001657
IP rating	IP68
Power draw (W)	7
UPC Code	879343001650
Connection	Plug connector
Current consumption (mA @ 12VDC)	0

Specifications

Stock status	Usually in stock
---------------------	------------------

Current consumption (mA @ 24VDC)	290
---	-----

Vessel size	20-50M
--------------------	--------

Min. feed wire gauge	0.5mm ² AWG22
-----------------------------	--------------------------

Weight (Kg)	1.32 Kg
--------------------	---------

Weight (Oz)	46.56 Oz
--------------------	----------