



## 5nm 225° Masthead, double black anodized, horizontal mount, with plug connector

300-038

5nm double masthead, horizontal mount  
W/aluminium base  
2 outlets at side and 2 outlets at bottom  
Base plate of HD PE for easy install

Specifications	
Number	300-038
Light Color	White
Dimensions metric	Ø92,5mm x 128mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
Intensity	>52cd
Dimensions imperial	Ø3.6" x 5"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	5nm
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	20-32VDC
EAN	5704438001756
IP rating	IP68
Power draw (W)	7
UPC Code	879343001759
Connection	Plug connector
Current consumption (mA @ 12VDC)	0

Specifications	
<b>Stock status</b>	Usually in stock
<b>Current consumption (mA @ 24VDC)</b>	290
<b>Vessel size</b>	20-50M
<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
<b>Weight (Kg)</b>	1.48 Kg
<b>Weight (Oz)</b>	52.20 Oz