



5nm 225° Masthead, double, black anodized, vertical mount, with 0,7m cable

300-039

5 nm dbl masthead vert CB mnt, 0.7m
Vertically mounted with 0.75m cable.

Specifications	
Number	300-039
Light Color	White
Dimensions metric	Ø92,5mm x 135mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>52cd
Dimensions imperial	Ø3.6" x 5.3"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	5nm
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	20-32VDC
EAN	5704438001749
IP rating	IP68
Power draw (W)	7
UPC Code	879343001742
Connection	0.7m cable
Current consumption (mA @ 12VDC)	0

Specifications	
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	290
Vessel size	20-50M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	1.35 Kg
Weight (Oz)	47.61 Oz