



6nm 225° Masthead + 3nm 360°white, silver anodized, horizontal mount, with plug connector

300-136+112G2

6nm masthead+ 3nm 360°white, hor mnt
Horizontally mounted on (400-034)
Cable side / cable down base.

Specifications	
Number	300-136+112G2
Light Color	White
Dimensions metric	Ø92,5mm x 129mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>15cd
Dimensions imperial	Ø3.6" x 5"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	20-32VDC
EAN	5704438015265
IP rating	IP68
Power draw (W)	13
UPC Code	879343015268
Connection	Plug connector
Current consumption (mA @ 12VDC)	0

Specifications	
Stock status	Made to order
Current consumption (mA @ 24VDC)	580
Vessel size	Over 50M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	2 Kg
Weight (Oz)	70.54 Oz