



## 2nm 112,5° port sidelight, single, vertical mount. Silver anodized. With 6m cable.

301-002 6M

This LED Navigation light comes in black and silver, with the best technology available and impressive robustness. It is easy to install. Below is a list of more great features. For more detailed information, please download technical files.

- For Boats and Yachts up to 50m (164 ft)
- High quality materials used for long life.
- Water and vibration proof.
- No EMC noise on your AIS/VHF.
- Multivoltage - 12 to 24 Volt.
- Worldwide approvals.
- Including potted-in power cable for ultimate waterproofness.
- 5 year warranty.

Vertically mounted with 6m cable

Specifications	
Number	301-002 6M
Light Color	Red
Dimensions metric	92,5 x 28 x 49,7
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
Intensity	>5.4cd
Dimensions imperial	3.6" x 1.1" x 1.95"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438012783
IP rating	IP68
Power draw (W)	1,2
UPC Code	879343012786
Connection	6m cable

Specifications	
<b>Current consumption (mA @ 12VDC)</b>	90
<b>Stock status</b>	Usually in stock
<b>Lead time</b>	1-2 weeks
<b>Current consumption (mA @ 24VDC)</b>	50
<b>Vessel size</b>	Under 12M,12-20M,20-50M
<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
<b>Weight (Kg)</b>	0.63 Kg
<b>Weight (Oz)</b>	22.22 Oz