



3nm 112,5° double starboard, silver anodized, vertical mount, with 2,5m cable

301-101ST

3nm dbl stbd, silver anodized
Vertical mounted with 2.5m cables

Specifications	
Number	301-101ST
Light Color	Green
Dimensions metric	100 x 100 x 49,7
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>15cd
Dimensions imperial	3.9" x 3.9" x 1.95"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light, precabled with 2.5 meter shielded marine grade cable, 2 Mounting screws (M6 * 8 mm), Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438013186
IP rating	IP68
Power draw (W)	2,3
UPC Code	879343013189
Connection	2.5m cable

Specifications	
Current consumption (mA @ 12VDC)	180
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	100
Vessel size	Over 50M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	1.02 Kg
Weight (Oz)	35.98 Oz