



3nm 112,5° port, silver anodized, vertical mount, with 2,5m cable

301-102

3nm port, silver anodized
Vertical mounted with 2.5m cable

| Specifications | |
|-----------------------|--|
| Number | 301-102 |
| Light Color | Red |
| Dimensions metric | 92,5 x 28 x 49,7 |
| Certification | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support |
| Intensity | >15cd |
| Dimensions imperial | 3.6" x 1.1" x 1.95" |
| Approved to | COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR |
| Visibility | 3nm |
| Included In Package | 1 Navigation light, precabled with 2.5 meter shielded marine grade cable, 2 Mounting screws (M6 * 8 mm), Installation guide |
| Operating temperature | -25°C to 55°C |
| Mounting | Vertical |
| Materials | Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane |
| Operating Voltage | 10-32VDC |
| EAN | 5704438010567 |
| IP rating | IP68 |
| Power draw (W) | 2 |
| UPC Code | 879343010560 |
| Connection | 2.5m cable |

| Specifications | |
|---|--------------------------|
| Current consumption (mA @ 12VDC) | 150 |
| Stock status | Usually in stock |
| Current consumption (mA @ 24VDC) | 100 |
| Vessel size | Over 50M |
| Min. feed wire gauge | 0.5mm ² AWG22 |
| Weight (Kg) | 0.39 Kg |
| Weight (Oz) | 13.76 Oz |