



## 3nm 135° stern, black anodized, horizontal mount, with plug connector

301-105-B

3nm stern (blk), hor mnt  
 Horizontally mounted on alu base & PE base plate  
 Cable direction side or bottom

Specifications	
Number	301-105-B
Light Color	White
Dimensions metric	Ø92,5mm x 74,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
Intensity	>15cd
Dimensions imperial	Ø3.6" x 2.9"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438010246
IP rating	IP68
Power draw (W)	1,7
UPC Code	879343010249
Connection	Plug connector

Specifications	
<b>Current consumption (mA @ 12VDC)</b>	130
<b>Stock status</b>	Usually in stock
<b>Current consumption (mA @ 24VDC)</b>	72
<b>Vessel size</b>	Over 50M
<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
<b>Weight (Kg)</b>	1 Kg
<b>Weight (Oz)</b>	35.27 Oz