



3nm 135° double stern, silver anodized, vertical mount, with 2,5m cable

301-106ST

3nm dbl stern, silver anodized
Vertical mounted with 2,5m cables

Specifications	
Number	301-106ST
Light Color	White
Dimensions metric	Ø92,5mm x 96,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>15cd
Dimensions imperial	Ø3.6" x 3.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438010659
IP rating	IP68
Power draw (W)	1,7
UPC Code	879343010652
Connection	2.5m cable
Current consumption (mA @ 12VDC)	130

Specifications	
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	72
Vessel size	Over 50M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	0.98 Kg
Weight (Oz)	34.56 Oz