140mA @ 12VDC 150mA @ 24VDC



PRINT TO SCALE!

MiniRail2 - LED Light

 \sim

Wire Exit Hole Drill Template



X

For 2-color operation with an external switch:

Light ramps in intensity over about 3 seconds.

To dim light interrupt this ramp with a brief Off/On toggle. This will stop the ramp and set the light at the desired intensity.

Subsequent Off/On toggles will change light color.

Light circuits should be protected with an appropriately sized fuse. Each light draws approximately 140mA at 12VDC and 150mA at 24VDC. Fuses on circuits with multiple lights should be sized accordingly.

Limited Warranty

Lumitec is not responsible for product failure caused by abuse, neglect, improper installation, or failure in applications other than those for which it was designed, intended, and marketed

This product is warranted to be free from defects in workmanship and materials for a period of one year from the date of original purchase. Should your Lumitec product prove defective during the warranty period promptly notify Lumitec and return product with freight prepaid. Lumitec will, at its option, repair or replace the product without charge for parts or labor, or refund purchase price. Products repaired or replaced under this warranty shall be warranted for the unexpired portion of the warranty applying to the original product(s). Lumitec is not responsible for product failure caused by abuse, neglect, improper installation, or failure in applications other than those for which it was designed, intended, and marketed. No warranty or affirmation of fact, express or implied, other than as set forth in the limited warranty statement above is made or authorized by Lumitec. Any liability for consequential and incidental damages is expressly disclaimed. Lumitec liability in all events is limited to, and shall not exceed, the purchase price paid.