

ProNauticP Series Selection



Model	ProNautic 1210P	ProNautic 1215P	ProNautic 1220P	ProNautic 1230P	ProNautic 1240P	ProNautic 1250P	ProNautic 1260P	ProNautic 2420P	ProNautic 2430P
Part #	63110	63115	63120	63130	63140	63150	63160	63170	63180
Volts	12	12	12	12	12	12	12	24	24
Amps	10 Amp	15 Amp	20 Amp	30 Amp	40 Amp	50 Amp	60 Amp	20 Amp	30 Amp
Banks	2 Bank	3 Bank	3 Bank	3 Bank	3 Bank	3 Bank	3 Bank	3 Bank	3 Bank
AC Input Voltage	100-260 Autoranging	100-260 Autoranging	100-260 Autoranging	100-260 Autoranging	100-260 Autoranging	100-260 Autoranging	100-260 Autoranging	100-260 Autoranging	100-260 Autoranging
Amperage at 100/240V AC	< 3.0 / < 1.5	< 4.0 / < 2.0	< 5.0 / < 2.5	< 6.0 / < 3.0	< 7.0 / < 3.5	< 10.0 / < 5.0	< 11.0 / < 5.5	< 7.0 / < 3.5	< 11.0 / < 5.5
Cycle	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60
Size (LxWxH)	10.25"x8.5"x 3.5"	10.25"x8.5"x 3.5"	10.25"x8.5"x 3.5"	10.25"x8.5"x 3.5"	10.25"x8.5"x 3.5"	12.25"x8.5"x 3.5"	12.25"x8.5"x 3.5"	10.25"x8.5"x 3.5"	12.25"x8.5"x 3.5"
Weight	5 lbs	5 lbs	5 lbs	5 lbs	5 lbs	7 lbs	7 lbs	5 lbs	7 lbs

Digitally Controlled Charge Profiles

Battery Type	12 Volt Models				24 Volt Models			
	Preset 1		Preset 2		Preset 1		Preset 2	
	Conditioning V DC	Auto Maintain V DC Range	Conditioning V DC	Auto Maintain V DC Range	Conditioning V DC	Auto Maintain V DC Range	Conditioning V DC	Auto Maintain V DC Range
Flooded	14.8V DC	12.8-13.6V DC	14.7V DC	12.8-13.4V DC	29.6V DC	25.6-27.2V DC	29.4V DC	25.6-26.8V DC
Sealed	14.4V DC	12.8-13.6V DC	14.6V DC*	12.8-13.4V DC*	28.8V DC	25.6-27.2V DC	29.2V DC*	25.6-26.8V DC*
AGM	14.4V DC	13.0-13.4V DC	14.6V DC	13.0-13.6V DC	28.8V DC	26.0-26.8V DC	29.2V DC	26.0-27.2V DC
GEL	14.0V DC	13.2-13.7V DC	14.4V DC	13.2-13.8V DC	28.0V DC	26.4-27.4V DC	28.8V DC	26.4-27.6V DC
LiFePO4 - Lithium	13.8V DC	13.2-13.8V DC	14.6V DC	13.2-14.6V DC	27.6V DC	26.4-27.6V DC	29.2V DC	26.4-29.2V DC
Calcium/Prgm Custom	15.1V DC	13.2-13.6V DC	PrgmV DC**	PrgmV DC**	30.2V DC	26.4-27.2V DC	PrgmV DC***	PrgmV DC***
Equalization	15.5V DC	15.5V DC	15.5V DC	15.5V DC	31.0V DC	31.0V DC	31.0V DC	31.0V DC

* Factory setting **Default : Conditioning = 13.6V DC, Auto Maintain = 13.2-13.6V DC ***Default: Conditioning = 27.2V DC, Auto Maintain = 26.4-27.2V DC



Remote Temperature Sensor Probe (included)

The ProNauticP comes standard with a temperature probe that is plug and play. Once the temperature sensor is connected the charger will adjust its charge based on the batteries temperature.

Part # 63106



Digital Display and Control Remote (optional)

ProNauticP optional remote available for interactive remote port for digital display and control.

Part # 63100

Related Products



ProIsoCharge Series page 36