



4MP Intensifier® IP Dome Camera with Advanced Analytics

O4iD2

2.8mm fixed lens, dark gray housing



Features

- Intensifier® Technology captures in full color in extreme low-light scenes
- Captures up to 4MP @ 30fps real time
- True WDR operation
- Micro SD card slot (card not included)
- Conformant with ONVIF Profile G/S/T
- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant
- Built-in standard PoE (IEEE 802.3af)
- Line crossing with counting/Intrusion detection*
- Face/Person/Vehicle detection*
- NDAA Compliant**
- Junction box included (works with NPT/BSP specifications)
- 5 year warranty



Included Junction Box

Camera Specifications

| | |
|--------------------------|---|
| Image Sensor | Progressive scan 1/1.8"CMOS |
| Maximum Resolution | 2560 × 1440 |
| Field of View | H.FoV: 110°; V.FoV:60°; D.FoV:130° |
| Minimum Illumination | 0.0006 lux@F1.0, AGC ON |
| White Balance | Auto, Indoor, Outdoor, Manual |
| Compensation | True WDR (120dB), BLC, HLC |
| Electronic Shutter Speed | 1s ~ 1/100000s |
| DNR | 3D DNR |
| Angle Adjustment | Pan: 0° ~ 355°; Tilt: 0° ~ 67°; Rotation: 0° ~ 355° |

Video Specifications

| | |
|--------------------|---|
| Main Resolution | 2560×1440/2304×1296/1920×1080/1280×720/D1/CIF/480×240 @30fps |
| Sub Stream | 1280×720/D1/CIF/480×240 @30fps |
| Third Stream | D1/CIF/480×240 @30fps |
| Compression | Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG |
| Video Settings | Region of Interest, Privacy masking, Brightness, Contrast, Hue, Saturation, Denoise, Antiflicker, Intensifier® presets, Exposure, Gain, Corridor Pattern, Image flip/mirror |
| Bitrate Control | VBR, CBR (64Kbps ~ 8Mbps) |
| Multiple Streaming | 3 streams |

Network Specifications

| | |
|--------------|---|
| Protocols | UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, UPnP, HTTP, HTTPS |
| DDNS support | Speco DDNS (free of charge) |
| Security | User ID & Password protection, IP/MAC address filtering, digest authentication |
| User Access | Max. 10 simultaneous users Actual number of users may vary depending on bandwidth |

Client Specifications

| | |
|---------------------|--|
| Web Browser Support | Google Chrome, Microsoft Edge, Internet Explorer, Apple Safari |
| PC Application | SecureGuard® VMS and SecureGuard® CMS |
| Mobile | SecureGuard® Client, Speco Blue |

Audio Specifications

| | |
|--------------|------------------------------|
| Audio Codec | G.711A / G.711U |
| Audio Input | Built-In Mic and 3.5mm Input |
| Audio Output | No |

Interfaces

| | |
|-----------|-------------------------------------|
| Ethernet | RJ45 Jack, 10/100 Mbps, PoE |
| Power | 12VDC input jack |
| Audio | Built-in mic and 3.5mm Input |
| Card Slot | MicroSD, up to 256GB (not included) |
| Alarm | 1 CH alarm input; 1 CH alarm output |
| Reset | Yes |

System Specifications

| | |
|----------------|---|
| PoE | Standard (IEEE 802.3af) |
| Analytics | Motion detection, region entrance/exiting/intrusion detection (human/vehicle classification), line crossing detection (human/vehicle classification), video tampering detection, scene change detection, face detection |
| Alarm Triggers | Motion detection, Sensor detection, SD card error, SD card full, IP address conflict, cable disconnection |
| Alarm Events | FTP upload, email upload |
| Image Settings | Watermark, IP address filtering, video mask, heartbeat, illegal login lock, image distortion correction |

Operating & Unit Specifications

| | |
|-----------------------|--|
| Power | PoE, 12VDC (power supply not included) |
| Power Consumption | 3.5W (max) |
| Operating Temperature | -40°F - 140°F |
| Operating Humidity | Less than 95% (non-condensing) |
| Unit Dimensions | 4.68" (φ) x 3.5" (H) |
| Unit Weight | 1.43 lbs |
| Certifications | FCC |

Cameras Interfaces



Optional Accessories



NDAA COMPLIANT *with compatible Speco Blue recorder
** Compliant with NDAA Section 889 Part B Guidelines

Onvif® | GSI



ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 3/9/23

Apps available from the following:



ONVIF® 800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • specotech.com

