

UNIQUE 'TRIPLE SEAL' LID ISOLATES ELECTRONICS FROM THE HARSH GRAY WASTE ENVIRONMENT FOR ADVANCED DURABILITY

- ▶ Integrated sensors for automatic pump control - solid state switch protected against water ingress
- ▶ Easy wiring - connect any 12V or 24V d.c. pump system (up to 20 amp with no relay required)
- ▶ Ports shaped for drilling accuracy (8 ltr and 20 ltr tanks only)
- ▶ Double switch models - second sensor can be wired to a high-level alarm or second pump
- ▶ Pumps can be top or side mounted on 20 ltr tank

8 LTRS / 2.1 US GAL MODEL



16 LTRS / 4.2 US GAL MODEL



20 LTRS / 5.3 US GAL MODEL



Models	Gray Waste Tanks											
PART NUMBER	GT0810B	GT0812B	GT0820B	GT0831B	GT1610B	GT1620B	GT1631B	GT2010B	GT2012B	GT2020B	GT2031B	
Voltage	12V / 24V d.c.											
Capacity	8 ltrs (2.1 US Gals)				16 ltrs (4.2 US Gals)				20 ltrs (5.3 US Gals)			
No. of sensors	1	2	2	1	1	2	1	1	2	2	1	
Electrical connections	Tinned wire ends		2 x Deutsch DT06-3S- P012	1x Deutsch DT06-3S- P012	Tinned wire ends		2 x Deutsch DT06-3S- P012	1x Deutsch DT06-3S- P012	Tinned wire ends		2 x Deutsch DT06-3S- P012	1x Deutsch DT06-3S- P012
Inlet hose connections	19mm (3/4") x 2, 25mm (1") x 3, 38mm (1 1/2") x 3				25mm (1") x 4, 38mm (1 1/2") x 4							
Outlet hose connections	19mm (3/4") x 1, 25mm (1") x 1				25mm (1") x 2							
Materials	Tank: MDPE, Seals: EPDM/Neoprene, Monprene®, Lid: Glass-filled Polypropylene, ABS, Polyurethane											
Service kits (Lid & sensor array)	AK1005	AK1008	AK1007	AK1006	AK1005	AK1007	AK1006	AK1005	AK1008	AK1007	AK1006	

TYPICAL INSTALLATION



FITTER FRIENDLY - CLEAR VISUAL CUES FOR INSTALLATION

TYPICAL INSTALLATION



DRILL LOCATOR PORTS