


## Double folding pad eye - Dia IO mm

Part #6566




### Description

Fully dropforged product with outstanding working and breaking loads regardless the angle of the load  
Perfect solution attachment (stay, blocks, jib tack point)  
Possibility to attach several stays  
Modern and optimized design to suit aesthetics of modern boats  
They can be fold down to minimize the risk of injuries  
The silicon pad eliminates noise and unpleasant vibrations

### Applications

For any fastening/attachment application  
Allows to attach several shrouds

## Technical information

Materials	316L stainless steel grade
 Working load (kg)	4560
Breaking load (kg)	9000
Weight (g)	494
A (mm)	75
B (mm)	45
C (mm)	23
d diameter (mm)	10.5
D diameter (mm)	10
E (mm)	104
F (mm)	78

### Caption



Working load (WL) : for nautical applications



Working Load Limit (WLL): for industrial applications only.  
The safety factor is 5 times the breaking load.  
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.