


## HR key pin shackle with bar - Dia 5 mm

Part #91432




### Description

Forged D shackle in HR stainless steel grade (17,4 PH)  
Outstanding working and breaking load  
A HR shackle can be up to 60% more resistant than a shackle in 316L stainless steel  
WLL: only for industrial applications (lifting i.e...)  
CE marking and batch number

### Applications

Applications requesting high loads  
Perfect product for halyards or applications requiring to open /close the shackle often  
Do not use for mooring applications

## Technical information

Materials	HR 17.4 PH stainless steel grade
 Working load (kg)	480
Breaking load (kg)	1500
Weight (g)	31
A (mm)	37
B (mm)	13
C (mm)	5
D (mm)	11
E (mm)	4
F (mm)	49
G (mm)	31
L (mm)	12

### Caption



Working load (WL) : for nautical applications



Working Load Limit (WLL): for industrial applications only.  
The safety factor is 5 times the breaking load.  
 $WLL = \text{Breaking load} / 5$

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.